



# BY396 THRU BY399

## FAST RECOVERY RECTIFIERS


Reverse Voltage - 100 to 800 Volts Forward Current - 3.0 Amperes

### FEATURES

The plastic package carries Underwriters Laboratory  
 Flammability Classification 94V-0  
 Fast switching for high efficiency  
 Low reverse leakage  
 High forward surge current capability  
 High temperature soldering guaranteed:  
 260°C/10 seconds, 0.375" (9.5mm) lead length,  
 5 lbs. (2.3kg) tension

### MECHANICAL DATA

**Case:** DO-201AD molded plastic body  
**Terminals:** Plated axial leads, solderable per MIL-STD-750,  
 Method 2026  
**Polarity:** Color band denotes cathode end  
**Mounting Position:** Any  
**Weight:** 0.012 ounce, 1.10 grams



### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.  
 Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

	SYMBOLS	BY396	BY397	BY398	BY399	UNITS
Maximum repetitive peak reverse voltage	$V_{RRM}$	100	200	400	800	V
Maximum RMS voltage	$V_{RMS}$	70	140	280	560	V
Maximum DC blocking voltage	$V_{DC}$	100	200	400	800	V
Maximum average forward rectified current 0.375" (9.5mm) lead length at $T_A=75^\circ\text{C}$	$I_{(AV)}$	3.0				A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	$I_{FSM}$	200.0				A
Maximum instantaneous forward voltage at 3.0A	$V_F$	1.3				V
Maximum DC reverse current $T_A=25^\circ\text{C}$ at rated DC blocking voltage $T_A=100^\circ\text{C}$	$I_R$	10.0 100.0				$\mu\text{A}$
Maximum reverse recovery time (NOTE 1)	$t_{rr}$	150			250	ns
Typical junction capacitance (NOTE 2)	$C_J$	60.0				pF
Typical thermal resistance (NOTE 3)	$R_{\theta JA}$	20.0				$^\circ\text{C/W}$
Operating junction and storage temperature range	$T_J, T_{STG}$	-55 to +150				$^\circ\text{C}$

**Note:** 1. Reverse recovery condition  $I_F=0.5\text{A}, I_R=1.0\text{A}, I_{rr}=0.25\text{A}$   
 2. Measured at 1MHz and applied reverse voltage of 4.0V D.C.  
 3. Thermal resistance from junction to ambient at 0.375" (9.5mm) lead length, P.C.B. mounted




®

# RATINGS AND CHARACTERISTIC CURVES BY396 THRU BY399


AVERAGE FORWARD RECTIFIED CURRENT, AMPERES

FIG. 1- FORWARD CURRENT DERATING CURVE




PEAK FORWARD SURGE CURRENT, AMPERES

FIG. 2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




INSTANTANEOUS FORWARD CURRENT, AMPERES

FIG. 3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




INSTANTANEOUS REVERSE CURRENT, MICROAMPERES

FIG. 4-TYPICAL REVERSE CHARACTERISTICS




JUNCTION CAPACITANCE, pF

FIG. 5-TYPICAL JUNCTION CAPACITANCE



TRANSIENT THERMAL IMPEDANCE, °C/W

FIG. 6-TYPICAL TRANSIENT THERMAL IMPEDANCE



t,PULSE DURATION,sec.